

CE 25			
tjm sistem Tim Sistem, Noma Pazova, Serbia		DoP No: 0017/16.12.25 EN 16510-1 / EN16510-2-3:2025 NB - 1015	
Residential space heating appliances fired by wood logs: wood cooker			
Model:		ROCCO	
Load bearing capacity:		0 kg	
Safety distance from combustible materials		mm	Bottom dB= 0 Floor in front dF = 1500 Ceiling dC = >750 Rear dR = 350 Side dS = 350 Side radiation area dL =1500 Front dP = 600
Emissions at : nominal heat output / reduced heat output		nominal	reduced
CO (at 13% O ₂)	mg/m ³	1244	/
Dust (at 13% O ₂)	mg/m ³	25	/
NOx (at 13% O ₂)	mg/m ³	100	/
OGC (at 13% O ₂)	mg/m ³	76	/
Data for installation on a chimney at: nominal heat output / reduced heat output		nominal	reduced
Flue gas outlet temperature	°C	200	/
Minimum flue draught	Pa	12	/
Flue gas mass flow	g/s	9,2	/
Data for installation on a chimney regarding fire safety	class	T400G	
Heat output and energy efficiency of the appliance at nominal heat output / reduced heat output		Nominal	Reduced
Space heat output at nominal / reduced heat output (room + water)	kW	9,9	
Energy efficiency at nominal / reduced heat output.	%	84,2	
Season efficiency	%	74,2	
EEL index / Energy class		112 / A +	
Power consumption at nominal heat output	kW	/	
Power consumption at reduced heat output	kW	/	
Power consumption in standby mode	kW	/	
Fuel consumption at nominal heat output	Kg / h	2,7	
Use only recommended fuels!			
Recommended fuel		Wood logs	
Type of appliance		TYPE B	
Max. water operating pressure	bar	/	
Suitability for installation to a shared flue system		yes	
Information about the appliance operation		Appliance for intermittent operation	
Fume exhaust	mm	Ø120	
Voltage	V	/	
Frequency	Hz	/	
Electrical connection		/	
Please read and follow the user operating instructions before starting!			
Serial number			